



MARITIME LLOYD

34 A, Off.3, Dimitry Tavadzebuli Str, Batumi 6000, Georgia

Tel: + 995 422 277537 ; Fax: + 995 422 277536.

E-mail: stat@geolloyd.com www.geolloyd.com

Circular No: 04 /05.02.2014

To :	Maritime Lloyd Authorized Surveyors
Dated:	05.02.2014
Subject:	Adoption of Amendments to the SOLAS 1974, Protocol of 1988 Chapter II-2, CONSTRUCTION – FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION, as per Resolution MSC.338(91)

Dear All,

As per IMO Resolution MSC.338(91), adoption of amendments to the SOLAS 1974, Chapter II-2, CONSTRUCTION – FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION will enter into the force from 1st of July 2014. Kindly find below text of new regulations:

Part A General

Regulation 1 – Application

The following footnote is added to the title of Regulation 1:

"*The application date of 1 July 2012 was introduced by resolution MSC.308(88). However, this resolution amended, under chapter II-2, regulations II-2/3.23 (definition of "Fire Test Procedures Code") and II-2/7.4.1 (new subparagraph .3) only, and all other regulations with the original application date of 1 July 2002 were not amended."

In the existing paragraph 2.4, the following new subparagraphs are added after the existing subparagraph .6:

".7 cargo ships of 500 gross tonnage and upwards and passenger ships constructed on or after 1 February 1992 but before 1 July 2002 need not comply with regulation 19.3.3 provided that they comply with regulation 54.2.3 as adopted by resolution MSC.13(57); and

".8 cargo ships of 500 gross tonnage and upwards and passenger ships constructed on or after 1 September 1984 but before 1 July 2002 need not comply with regulations 19.3.1, 19.3.5, 19.3.6, 19.3.9, provided that they comply with regulations 54.2.1, 54.2.5, 54.2.6, 54.2.9 as adopted by resolution MSC.1(XLV)."

The following new paragraph 2.5 is added:

"2.5 Ships constructed before 1 July 2012 shall also comply with regulation 10.1.2, as adopted by resolution MSC.338(91)."

Part C
Suppression of fire
Regulation 9 – Containment of fire

In table 9.3, column (11) (Special category and ro-ro spaces), row (2) (Corridors), the symbol "A-15" is replaced by the symbol "A-30g".

In table 9.3, column (11) (Special category and ro-ro spaces), row (4) (Stairways), the symbol "A-15" is replaced by the symbol "A-30g".

In table 9.3, column and row (11) (Special category and ro-ro spaces), the symbol "A-0" is replaced by the symbol "A-30g".

In table 9.4, column (11) (Special category and ro-ro spaces), row (1) (Control stations), the symbol "A-30" is replaced by the symbol "A-60 g".

In table 9.4, column (11) (Special category and ro-ro spaces), row (2) (Corridors), the symbol "A-0" is replaced by the symbol "A-30g".

In table 9.4, column (11) (Special category and ro-ro spaces), row (4) (Stairways), the symbol "A-0" is replaced by the symbol "A-30 g".

In table 9.4, column and row (11) (Special category and ro-ro spaces), the symbol "A-0" is replaced by the symbol "A-30g".

In table 9.4, column (2) (Corridors), row (11) (Special category and ro-ro spaces), the symbol "A-15" is replaced by the symbol "A-30 g".

In table 9.4, column (4) (Stairways), row (11) (Special category and ro-ro spaces), the symbol "A-15" is replaced by the symbol "A-30g".

In table 9.4, column (6) (Machinery spaces of category A), row (11) (Special category and ro-ro spaces), the symbol "A-30" is replaced by the symbol "A-60 g".

In table 9.4, a new note is added as follows:

"g - Ships constructed before 1 July 2014 shall comply, as a minimum, with the previous requirements applicable at the time the ship was constructed, as specified in regulation 1.2."

In table 9.5, column and row (11) (Ro-ro and vehicle spaces), the symbol "*_h" is replaced by the symbol "A-30 j".

In table 9.6, column (11) (Ro-ro and vehicle spaces), row (10) (Open decks), the symbol "*" is replaced by the symbol "A-0 j".

In table 9.6, column and row (11) (Ro-ro and vehicle spaces), the symbol "*_h" is replaced by the symbol "A-30 j".

In table 9.6, column (10) (Open decks), row (11) (Ro-ro and vehicle spaces), the symbol "*" is replaced by the symbol "A-0 j".

In table 9.6, the existing text of note "h" is replaced with the word "deleted".

In table 9.6, a new note is added as follows:

"j - Ships constructed before 1 July 2014 shall comply, as a minimum, with the previous requirements applicable at the time the ship was constructed, as specified in regulation 1.2."

Paragraphs 6.2 and 6.3 are deleted and the subsequent paragraphs are renumbered accordingly.

Regulation 10 – Fire fighting

In paragraph 5.6.3, the existing subparagraph .1 is replaced by the following:

".1 the fire hazard portions of internal combustion machinery or, for ships constructed before 1 July 2014, the fire hazard portions of internal combustion machinery used for the ship's main propulsion and power generation;"

The existing paragraph 10.1 is replaced by the following:

"10.1 Types of firefighter's outfits

.1 Fire-fighter's outfits shall comply with the Fire Safety Systems Code; and
.2 Self-contained compressed air breathing apparatus of fire-fighter's outfits shall comply with paragraph 2.1.2.2 of chapter 3 of the Fire Safety Systems Code by 1 July 2019."

After the existing paragraph 10.3, the following new paragraph is added:

"10.4 Fire-fighter's communication

For ships constructed on or after 1 July 2014, a minimum of two two-way portable radiotelephone apparatus for each fire party for fire-fighter's communication shall be carried on board. Those two-way portable radiotelephone apparatus shall be of an explosion-proof type or intrinsically safe. Ships constructed before 1 July 2014 shall comply with the requirements of this paragraph not later than the first survey after 1 July 2018."

Part E

Operational requirements

Regulation 15 – Instructions, onboard training and drills

After the existing paragraph 2.2.5, the following new paragraph is added:

"2.2.6 An onboard means of recharging breathing apparatus cylinders used during drills shall be provided or a suitable number of spare cylinders shall be carried on board to replace those used."

Part G

Special requirements

Regulation 20 – Protection of vehicle, special category and Ro-Ro spaces

The existing paragraph 6.1, including paragraphs 6.1.1 and 6.1.2, are replaced by the following:

"6.1 Fixed fire-extinguishing systems

(The requirements of paragraphs 6.1.1 and 6.1.2 shall apply to ships constructed on or after 1 July 2014. Ships constructed before 1 July 2014 shall comply with the previously applicable requirements of paragraphs 6.1.1 and 6.1.2.)

6.1.1 Vehicle spaces and Ro-Ro spaces, which are not special category spaces and are capable of being sealed from a location outside of the cargo spaces, shall be fitted with one of the following fixed fire-extinguishing systems:

- .1 a fixed gas fire-extinguishing system complying with the provisions of the Fire Safety Systems Code;
- .2 a fixed high-expansion foam fire-extinguishing system complying with the provisions of the Fire Safety Systems Code; or
- .3 a fixed water-based fire fighting system for Ro-Ro spaces and special category spaces complying with the provisions of the Fire Safety Systems Code and paragraphs 6.1.2.1 to 6.1.2.4.

6.1.2 Vehicle spaces and Ro-Ro spaces not capable of being sealed and special category spaces shall be fitted with a fixed water-based fire-fighting system for Ro-Ro spaces and special category spaces complying with the provisions of the Fire Safety Systems Code which shall protect all parts of any deck and vehicle platform in such spaces. Such a water-based fire-fighting system shall have:

- .1 a pressure gauge on the valve manifold;
 - .2 clear marking on each manifold valve indicating the spaces served;
 - .3 instructions for maintenance and operation located in the valve room; and
 - .4 a sufficient number of drainage valves to ensure complete drainage of the system."
-

Kindly confirm the understanding of the Circular and receipt of amended templates by signing the corresponding form attached.

Kindly be informed.

Best Regards,
Ellen Rukhadze
Chief Executive Officer
Maritime Lloyd

